正式图 | 参考图 | CUSTOMER DRAWING | The requirements of environmental protection | ROHS2 | Halogen free

Mark	ECN NO.	DESCRIPTION	DESIGN	Date:
——	——	NEW VERSION	David Zhou	2013.12.24







NOTES:
1.Signal transmission speed:Max25Mbps
2. Operating voltage:2.7 to5.5v
3. TTLand high C-MOS LOGIC compatible
4. Low power consumption
5. Operating temperrature:-20° to 70°
6. Storage temperrature:-30° to 80°
7.Soldering temperature:260°,time for 5s

Pin Function	
Tx	Rx
① Vin	① Vcc
② Vcc	② GND
③ GND	③ Vout





Recommended P.C.Board hole

P/N:
TR1026W-XXXX-00A0XXB
- MODEL NO
- PLASTIC MATERIAL
  - B0:PBT 30%G/F UL94V-0
  - D0:PA66 30%G/F UL94V-0
- AUTOMATIC DOOR COLOR
  - 01:BLACK
  - 08:GRAY
  - 10:ORANGE1575C
- PACKING:TRAY
- SIGNAL SPEC:
  - T0:TRANSMIT SPEED 16Mbps
  - T1:TRANSMIT SPEED 25Mbps
  - R0:RECEIVE SPEED 16Mbps
  - R1:RECEIVE SPEED 25Mbps

NO.	DESCRIPTION	QTY	MATERIAL	PLATING OR COLOR
5	OPTICAL FIBER	1	——	Ag
4	SPRING COIL	1	STAINLESS STEEL	——
3	BASE	1	PA66 30%G/F UL94V-0	BLACK
2	GATE	1	PA66 30%G/F UL94V-0	CHOOSE FROM P/N:
1	HOUSING	1	PA66 30%G/F UL94V-0	BLACK

TABLE E : Parts of Product

Tolerance X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 Angle ±3.0°	MODEL NAME:OPTICAL JACK MODEL No:TR1026W-XXXX-00A0XXB	DRAWING: David Zhou CHECKED: David Zhou
SCALE:1:1 / REVISION A0 / SHEET 1/1		APPROVED:Jacky Lee DATE: 2013.12.24
UNIT:mm	菱揚精密有限公司 Ling Yang Precision Co.,Ltd	FILE:CD/LINGYANG DWG NO. TR1026W-A001