





SECTION A-A
SCALE 1:1



- Note:
- Material:
 - Housing: thermoplastic high temp.UL94V-0; Color: see P/N.
 - Latch: thermoplastic high temp.UL94V-0; Color: see P/N.
 - Terminal: copper alloy.
 - Fitting Nail: copper alloy.
 - Finsh:
 - Terminal: Underplating: Au/matt Tin overall.
 - Fitting Nail: Underplating: matt Tin overall.
 - Product must comply HF RoHS specification.

Table A

CKTS	DIM A	DIM B	DIM C	DIM D
4	1.50	2.60	5.50	5.95
5	2.00	3.10	6.00	6.45
6	2.50	3.60	6.50	6.95
7	3.00	4.10	7.00	7.45
8	3.50	4.60	7.50	7.95
9	4.00	5.10	8.00	8.45
10	4.50	5.60	8.50	8.95
11	5.00	6.10	9.00	9.45
12	5.50	6.60	9.50	9.95
13	6.00	7.10	10.00	10.45
14	6.50	7.60	10.50	10.95
15	7.00	8.10	11.00	11.45
16	7.50	8.60	11.50	11.95
17	8.00	9.10	12.00	12.45
18	8.50	9.60	12.50	12.95
19	9.00	10.10	13.00	13.45
20	9.50	10.60	13.50	13.95
21	10.00	11.10	14.00	14.45
22	10.50	11.60	14.50	14.95
23	11.00	12.10	15.00	15.45
24	11.50	12.60	15.50	15.95
25	12.00	13.10	16.00	16.45
26	12.50	13.60	16.50	16.95
27	13.00	14.10	17.00	17.45
28	13.50	14.60	17.50	17.95
29	14.00	15.10	18.00	18.45
30	14.50	15.60	18.50	18.95
31	15.00	16.10	19.00	19.45
32	15.50	16.60	19.50	19.95
33	16.00	17.10	20.00	20.45
34	16.50	17.60	20.50	20.95
35	17.00	18.10	21.00	21.45
36	17.50	18.60	21.50	21.95
37	18.00	19.10	22.00	22.45
38	18.50	19.60	22.50	22.95
39	19.00	20.10	23.00	23.45
40	19.50	20.60	23.50	23.95
41	20.00	21.10	24.00	24.45
42	20.50	21.60	24.50	24.95
43	21.00	22.10	25.00	25.45
44	21.50	22.60	25.50	25.95
45	22.00	23.10	26.00	26.45
46	22.50	23.60	26.50	26.95
47	23.00	24.10	27.00	27.45
48	23.50	24.60	27.50	27.95
49	24.00	25.10	28.00	28.45
50	24.50	25.60	28.50	28.95
51	25.00	26.10	29.00	29.45
52	25.50	26.60	29.50	29.95
53	26.00	27.10	30.00	30.45
54	26.50	27.60	30.50	30.95
55	27.00	28.10	31.00	31.45
56	27.50	28.60	31.50	31.95
57	28.00	29.10	32.00	32.45
58	28.50	29.60	32.50	32.95
59	29.00	30.10	33.00	33.45
60	29.50	30.60	33.50	33.95

- AFC240H-XXXX-XXXXXXX
- Model P/N
 - Plastical Material: LCP UL94V-0
 - Housing Color: 0:Natural, 1:Black, 3:White
 - Latch Color: 0:Natural, 1:Black, 3:White
 - Packing: R:Tape reel, T:Tube
 - Remark: H:Halogen & RoHS2, R:RoHS2
 - Contact type: E:Upper, F:Lower
 - Plating Code: A1:Gold flash 1u", A2:Gold flash 2u", A3:Gold flash 3u", A4:Bright-Tin 90-120u", A4:Matt-Tin 90-120u"
 - CKTS: See Table A

Tolerance	MODEL NAME: 0.5Pitch H=2.0 FPC Easy-on Back-Flip R/A Type1 SMT CONN	DRAWING: Carlyle Xu
X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 Angle ±3.0°	MODEL No:AFC240H-CO01-XXXXFHX	CHECKED: David Zhou
	SCALE: 1:1	REVISION: A0
		SHEET: 1/1
UNIT:mm	菱揚精密有限公司 Ling Yang Precision Co.,Ltd	APPROVED: Jacky Lee
		DATE: 2015.02.26
		FILE: F/LINGYANG
		DWG NO.AFC170H-A001